



B. J. WOLFE ENTERPRISES, INC.

(818) 889-8412, (800) 554-1224, Fax (818) 889-8417

Extermination Heat Treatment Equipment

Model 875 Handheld Thermometer

875F

- Battery Operated
- Single Input with LCD Display
- Reads -112.0°F to +199.9°F with 0.1°F Resolution
+200.0°F to +752.0°F with 1°F Resolution
- Accepts Type "T" Thermocouples with Miniature Male Connector
- Warranty-One Year



Model 8052-Six Channel Switch Box

- Turns Single Channel 875F into Six Channel Digital Thermometer
- Plugs Into the Top of the 875F
- Quick Selection of Reading for 1-6 Probes
- Warranty-One Year

Thermocouples-The Heat Sensors-Wires

8052

BJWE has developed a low-cost thermocouple to measure the temperature in the treated rooms, and inside the walls. The T24S-PVC probes are 24 gauge, stranded, type "T" thermocouple wire, with a color coded PVC insulation over each conductor and a brown overall jacket. The thermocouple wire is cut to length, welded (beaded) on the sensing end, and a miniature male plug (connector) is attached to the cold end which plugs into the 875F or 8052. Operating temperature is 220°F



Commonly Used Thermocouple Part Number

Part Number	Footage
T24S-PVC-25FT-MCM	25 Feet
T24S-PVC-50FT-MCM	50 Feet
T24S-PVC-75FT-MCM	75 Feet
T24S-PVC-100FT-MCM	100 Feet

Any length available, please call for part number and pricing.

Quantity Discounts

1-9 Net	20-29 10%
10-19 5%	30+ 15%

Athena Controls • Doric • Fluke • Partlow-Danaher • Tegam • Watlow