



B. J. WOLFE ENTERPRISES, INC.

(818) 889-8412, (800) 554-1224, Fax (818) 889-8417

24-Hour Delivery

24-Hour Delivery

Low-Cost Thermocouple Assemblies

“Washer Thermocouples”

Washer thermocouples are an excellent low-cost solution to measure surface temperature with a 24-Hour delivery (or better). These thermocouples consist of insulated thermocouple grade wire cut to length, with a weld on one end. After forming the welded end into a circle by using a special Tungsten Inert Gas Welder in an argon atmosphere, a second weld strengthens the joint. The junction is then placed into the washer assembly for folding and crimped to the thermocouple wire. Stripped leads are standard, however compensated spade lugs, and connectors are available. Number eight (#8) washer uses 24 gauge solid wire, number ten (#10) and above use 20 gauge solid wire.



<table border="1"> <thead> <tr> <th colspan="2">T/C Wire Insulation</th> </tr> <tr> <th>Enter</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>WTG</td> <td>Glass (900°F)</td> </tr> <tr> <td>WTT</td> <td>PFA Teflon™ (500°F)</td> </tr> </tbody> </table>	T/C Wire Insulation		Enter	Description	WTG	Glass (900°F)	WTT	PFA Teflon™ (500°F)	<table border="1"> <thead> <tr> <th colspan="4">Washer Size</th> </tr> <tr> <th>Enter</th> <th>Description</th> <th></th> <th></th> </tr> <tr> <th></th> <th>Screw Size</th> <th>I.D.</th> <th>O.D.</th> </tr> </thead> <tbody> <tr> <td>8</td> <td>#8</td> <td>0.180</td> <td>0.325</td> </tr> <tr> <td>10</td> <td>#10</td> <td>0.200</td> <td>0.420</td> </tr> <tr> <td>14</td> <td>1/4"</td> <td>0.260</td> <td>0.575</td> </tr> <tr> <td>16</td> <td>5/16"</td> <td>0.320</td> <td>0.700</td> </tr> </tbody> </table>	Washer Size				Enter	Description				Screw Size	I.D.	O.D.	8	#8	0.180	0.325	10	#10	0.200	0.420	14	1/4"	0.260	0.575	16	5/16"	0.320	0.700	<table border="1"> <thead> <tr> <th colspan="2">Termination</th> </tr> <tr> <th>Enter</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>STL</td> <td>Std Stripped Leads</td> </tr> <tr> <td>LUG</td> <td>Compensated Spade Lugs</td> </tr> <tr> <td>MC-M</td> <td>Miniature Male Plug</td> </tr> <tr> <td>MC-F</td> <td>Miniature Female Jack</td> </tr> <tr> <td>SC-M</td> <td>Standard Male Plug</td> </tr> <tr> <td>SC-F</td> <td>Standard Female Jack</td> </tr> </tbody> </table>	Termination		Enter	Description	STL	Std Stripped Leads	LUG	Compensated Spade Lugs	MC-M	Miniature Male Plug	MC-F	Miniature Female Jack	SC-M	Standard Male Plug	SC-F	Standard Female Jack
T/C Wire Insulation																																																						
Enter	Description																																																					
WTG	Glass (900°F)																																																					
WTT	PFA Teflon™ (500°F)																																																					
Washer Size																																																						
Enter	Description																																																					
	Screw Size	I.D.	O.D.																																																			
8	#8	0.180	0.325																																																			
10	#10	0.200	0.420																																																			
14	1/4"	0.260	0.575																																																			
16	5/16"	0.320	0.700																																																			
Termination																																																						
Enter	Description																																																					
STL	Std Stripped Leads																																																					
LUG	Compensated Spade Lugs																																																					
MC-M	Miniature Male Plug																																																					
MC-F	Miniature Female Jack																																																					
SC-M	Standard Male Plug																																																					
SC-F	Standard Female Jack																																																					
<table border="1"> <thead> <tr> <th colspan="2">Thermocouple Type</th> </tr> <tr> <th>Enter</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>J</td> <td>Iron/Constantan</td> </tr> <tr> <td>K</td> <td>CHROMEL®/ALUMEL®</td> </tr> <tr> <td>T</td> <td>Copper/Constantan</td> </tr> <tr> <td>E</td> <td>CHROMEL®/Constantan</td> </tr> </tbody> </table>	Thermocouple Type		Enter	Description	J	Iron/Constantan	K	CHROMEL®/ALUMEL®	T	Copper/Constantan	E	CHROMEL®/Constantan	<table border="1"> <thead> <tr> <th colspan="2">Length of Washer Thermocouple</th> </tr> <tr> <th>Enter</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td></td> <td>Specify in Inches</td> </tr> </tbody> </table>	Length of Washer Thermocouple		Enter	Description		Specify in Inches	<table border="1"> <thead> <tr> <th colspan="2">Special Options</th> </tr> <tr> <th>Enter</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td></td> <td>None Leave Blank</td> </tr> <tr> <td>STR</td> <td>Stranded T/C Wire Used</td> </tr> <tr> <td>SB</td> <td>Stainless Steel Overbraiding</td> </tr> <tr> <td>SPL</td> <td>Special Limit of Error Wire</td> </tr> </tbody> </table>	Special Options		Enter	Description		None Leave Blank	STR	Stranded T/C Wire Used	SB	Stainless Steel Overbraiding	SPL	Special Limit of Error Wire																						
Thermocouple Type																																																						
Enter	Description																																																					
J	Iron/Constantan																																																					
K	CHROMEL®/ALUMEL®																																																					
T	Copper/Constantan																																																					
E	CHROMEL®/Constantan																																																					
Length of Washer Thermocouple																																																						
Enter	Description																																																					
	Specify in Inches																																																					
Special Options																																																						
Enter	Description																																																					
	None Leave Blank																																																					
STR	Stranded T/C Wire Used																																																					
SB	Stainless Steel Overbraiding																																																					
SPL	Special Limit of Error Wire																																																					

Pricing Includes:
 12" leads, "STL" Stripped Lead Termination
 Choice of Washer Size
 PFA Teflon™ or Fiberglass Insulation
 Consult for Quantity Discounts and Special Option Pricing

CHROMEL® and ALUMEL® trademarks of Hopkins Manufacturing Company. Teflon™ trademark of DuPont.